



深圳市中电高能电源科技有限公司
SZ Power Technology Co.,Ltd

Your
Professional
ODM Partner



深圳市中电高能电源科技有限公司
SZ Power Technology Co.,Ltd

+86 755 2877 8541

+86 15814796322


15814796322

powersuppliesales

sales@cctvpowersupply.cn

深圳市龙华区观湖街道松元厦社区环观中路102号厂房201

Plant building 201, Huanguan Zhong Road 102, Songyuanxia Community,
Guanhu Street, Longhua District, ShenZhen, China



SZpower >



01 ABOUT US

SZ Power Technology Co., Ltd

Was founded in 2007. It is a private enterprise with 15 years experience in power supply products. Over the years, we focus on R&D, production and sales of various power supply products such as Travel Charger ,Car charger, Wireless Charger, LED Power Supply, and CCTV Power Supply.

Our company ensures product quality by strictly adhering to ISO9001:2015 quality management standards and our professional R&D team with high efficient execution and responsibility to meet special demands and new ideas of clients. All of our products are UL, Efficiency VI(DOE 6), CE(EMC, LVD), FCC, GS, IEC, ROHS, SAA approved.

Depending on the strong technical strength, superior product quality and reasonable market price, SZ Power products have accumulated the good public praise and reputation gradually. Our products were sold in more than 80 countries and regions so far.

Welcome any enquiry from you and start our friendly cooperation.



02 Certificates

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L467376-20X3A6005-40909102-1
Report Reference E467376-A6005-UL
Date 22-Mar-2021

Issued to: SZ Power Technology Co Ltd
 A F5 Building No.0100028
 Xixue Industrial Area Xixihu Community
 Guanlan Longhua New District Shenzhen , Guangdong,
 China 518109

This is to certify that representative samples of QQJQ - Power Supplies for Use with Audio/Video, Information and Communication Technology Equipment
 See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.


Standard(s) for Safety: UL 62368-1, 2nd Ed., Issue Date: 2014-12-01

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



UL LLC
 Any information and documentation including UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at info@ul.com



GaN Technology

Light Weight & Small Size






High Efficiency



Low Heat



Safe

SZ-65W1P-G



65W
High Power



GaN
Technology



2*USB C ports
1*USB A port



Multi-prot
Charger



SZ-65W3P-G



GaN 65W 1 Port PD Charger

1*USB-C port Size: 53.5*53.5*31mm
Power Delivery Texture Surface

- > Input: AC 100V ~ 240V, 50/60 Hz, 1.8A
- > Total Output: 65W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V 3.25A

03

04



GaN 65W 3 Ports PD Charger

2*USB C ports & 1* USB A port Size: 60*60*31.5mm
Power Delivery & Quick Charge 3.0 Texture Surface

- > Input: AC 100V ~ 240V, 50/60 Hz, 1.8A
- > Total Output: 65W Max
- > Output 1: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V 3.25A, 65W Max
- > Output 2: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V 3.25A, 65W Max
- > Output 3: QC3.0: 3.6V~12V, 3A Max, 18W Max
- > C1+C2=PD45W+PD20W; C1+A=PD45W+18W
- > C2+A=PD45W+18W; C1+C2+A=PD27W+PD20W+18W

GaN 100W High Power Fast Charger

New material, New security protection



High Efficiency



Low Heat



Safe

SZ-100W1P-G



140W
Power Delivery



GaN
Technology



Foldable



Short-circuit
Protection

SZ-140W1P-G



GaN 100W 1Port PD Charger

1*USB-C port Size: 65.5*65.5*35mm
Power Delivery Texture Surface

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 100W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V 5A

05

06



GaN 140W 1Port PD Charger

1*USB-C port Size: 65.5*65.5*35mm
Power Delivery Texture Surface

- > Input: AC 100-240VAC, 50/60Hz, 2.0A
- > Total Output: 140W Max
- > Output: PD3.1: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V5A; 28V5A



SZ-18W-PQ



SZ-20W-PQ



USB-C PD 18W

1*USB-C port Size: 50.5*49*28.5mm
Power Delivery Highlight Surface

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 18W Max
- > Output: PD3.0: 5V 3A; 9V 2A; 12V 1.5A
- > Certificates: UL, FCC, CB, CE, VI(CEC, ERP)



USB-C PD 20W

1*USB-C port Size: 50.5*49*28.5mm
Power Delivery Highlight Surface

- > Input: AC 100V~240V, 50/60 Hz, 0.7A
- > Total Output: 20W Max
- > Output: PD3.0: 5V 3A; 9V 2.22A; 12V 1.67A
- > Certificates: UL, FCC, CB, CE, VI(CEC, ERP)



SZ-30W-PQ-W



SZ-30W-Q-W



USB-C PD 30W

1*USB-C port Size: 62.8*65*29mm
Power Delivery Highlight Surface

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 30W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 2.5A; 15V 2A; 20V 1.5A
- > Certificates: UL, FCC, CB, CE, VI(CEC, DoE, ERP)

09

10



DUAL USB-A 30W

2*USB-A ports Size: 62.8*65*29mm
Quick Charge 3.0 Highlight Surface

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 30W Max
- > Output 1: QC3.0: 3.6V~12V(QC 0.2V/Step), 3.6~6.5V/3A, 6.5~9V/2A, 9~12V/1.5A
- > Output 2: 5V 2.4A
- > Certificates: UL, FCC, CB, CE, VI(CEC, DoE, ERP)



SZ-45W-PQ



SZ-48W-PQ



USB-C PD 45W

1*USB-C port Size: 62.8*65*29mm
Power Delivery Highlight Surface

- > Input: AC 100V ~ 240V, 50/60 Hz, 1.5A
- > Total Output: 45W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V 2.25A
- > Certificates: UL, FCC, CB, CE, VI(CEC, DoE, ERP)

11

12



USB-C & USB A 48W

1*USB-C port & 1*USB-A port Size: 63.8*66*29mm
Power Delivery & Quick Charge 3.0 Highlight Surface

- > Input: AC 100V ~ 240V, 50/60 Hz, 1.5A
- > Total Output: 48W Max
- > Output 1: PD3.0: 5V 3A; 9V 3A; 12V 2.5A; 15V 2A; 20V 1.5A
- > Output 2: QC3.0: 3.6V~12V(QC 0.2V/Step), 3.6~6.5V/3A, 6.5~9V/2A, 9~12V/1.5A
- > Certificates: UL, FCC, CB, CE, VI(CEC, DoE, ERP)



SZ-61W-PQ



SZ-61W-PQ fixing C-C cable 1.5m



USB-C PD 61W

1*USB-C port Size: 79*76.5*29.5mm
Power Delivery Highlight Surface

- > Input: AC 100V ~ 240V, 50/60 Hz, 1.5A
- > Total Output: 61W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V/20.3V 3A
- > Certificates: UL, FCC, CB, CE, PSE, VI(CEC, DoE, ERP)

13

14



USB-C PD 61W

1*USB-C port Size: 79*76.5*29.5mm
Power Delivery Highlight Surface

- > Input: AC 100V ~ 240V, 50/60 Hz, 1.5A
- > Total Output: 61W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V/20.3V 3A
- > Certificates: UL, FCC, CB, CE, PSE, VI(CEC, DoE, ERP)



SZ-87W-PQ



SZ-87W-PQ

fixing C-C cable 1.5m



USB-C PD 87W

1*USB-C port Size: 79*76.5*29.5mm
Power Delivery Highlight Surface

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 87W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20.3V 4.35A
- > Certificate: CE

15

16



USB-C PD 87W

1*USB-C port Size: 79*76.5*29.5mm
Power Delivery Highlight Surface

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 87W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20.3V 4.35A
- > Certificate: CE



SZ-100W-PQ



SZ-100W-PQ fixing C-C cable 1.5m



USB C PD 100W

1*USB-C port Size: 79*76.5*29.5mm
Power Delivery Highlight Surface

- > Input: AC 100-240V, 50/60Hz, 2.0A
- > Total Output: 100W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V 5A

17

18



USB C PD 100W

1*USB-C port Size: 79*76.5*29.5mm
Power Delivery Highlight Surface

- > Input: AC 100-240V, 50/60Hz, 2.0A
- > Total Output: 100W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V 5A

SZ-30W-PQ-W

(With Exchangeable Plugs)

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 30W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 2.5A; 20V 1.5A
- > Certificates: UL, FCC, CB, CE, VI(CEC, DoE, ERP)

SZ-45W-PQ

(With Exchangeable Plugs)

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 45W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V 2.25A
- > Certificates: UL, FCC, CB, CE, VI(CEC, DoE, ERP)

SZ-87W-PQ

(With Exchangeable Plugs)

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 87W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20.3V 4.35A
- > Certificate: CE

SZ-48W-PQ

(With Exchangeable Plugs)

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 48W Max
- > Output 1: PD3.0: 5V 3A; 9V 3A; 12V 2.5A; 15V 2A; 20V 1.5A
- > Output 2: QC3.0: 3.6V~12V(QC 0.2V/Step), 3.6~6.5V/3A, 6.5~9V/ 2A, 9~12V/ 1.5A
- > Certificates: UL, FCC, CB, CE, VI(CEC, DoE, ERP)

SZ-100W-PQ

(With Exchangeable Plugs)

- > Input: AC100~240V, 50/60Hz, 2.0A Max
- > Total Output: 100W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V 5A

SZ-61W-PQ

(With Exchangeable Plugs)

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 61W Max
- > Output: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V/20.3V 3A
- > Certificates: UL, FCC, CB, CE, PSE, VI(CEC, DoE, ERP)



19

20





SZ-75W-PQ

Multi-ports 75W

1*USB-C port & 2*USB-A ports Size: 100*81*32mm
Power Delivery & Quick Charge 3.0 Paint Spraying

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 75W Max
- > Output 1: QC3.0: 3.6V~12V(QC 0.2V/Step), 3.6~6.5V/3A, 6.5~9V/2A, 9~12V/1.5A
- > Output 2: 5V 2.4A
- > Output 3: PD3.0: 5V 3A; 9V 3A; 12V 3A; 15V 3A; 20V 2.25A
- > Certificates: UL, FCC, CB, CE, VI(CEC, DoE, ERP)

21

22

SZ-83W-LPQ



Laptop Charger 83W

1*DC & 1* USB-A port Size: 120*65*25mm
Quick Charge 3.0 Paint Spraying

- > Input: AC 100V~240V, 50/60 Hz, 1.5A
- > Total Output: 83W Max
- > Output 1: DC 19.5V 3.25A
- > Output 2: QC3.0: 3.6V~12V(QC 0.2V/Step), 3.6~6.5V/3A, 6.5~9V/2A, 9~12V/1.5A
- > Certificates: UL, FCC, CB, CE, VI(CEC, DoE, ERP)



DC5V Power Adapter

- > Input: AC 100V-240V, 50/60 Hz
- > Output: DC5V 2.4A
- > Power: 12W
- > Output Plug: 10*5.5*2.1mm
(Accept Customization)
- > Certificates: UL, CB, CE, FCC, VI(CEC, DoE, ERP)

cUL62368, EN62368
Efficiency: Level VI(CEC, DoE, ERP)
Small Stature, Large Energy

DC24V Power Adapter

- > Input: AC 100V-240V, 50/60 Hz
- > Output: DC24V 0.5A-2A
- > Power: 12W/24W/48W
- > Output Plug: 10*5.5*2.1mm
(Accept Customization)
- > Certificates: UL, CB, CE, FCC, VI(CEC, DoE, ERP)

23

24

DC12V Power Adapter

- > Input: AC 100V-240V, 50/60 Hz
- > Output: DC12V 1A-5A
- > Power: 12W/24W/36W/48W/60W
- > Output Plug: 10*5.5*2.1mm
(Accept Customization)
- > Certificates: UL, CB, CE, FCC, VI(CEC, DoE, ERP)

